## TITAN 2208-G4 GPU server



Increase Performance and Productivity.



## TITAN 2208-G4

Our TITAN systems are designed for GPU-accelerated computing and to speed up your most demanding enterprise, HPC and hyperscale data center workloads. Increase research productivity, accelerate your deep learning, Al, visualization and simulation applications with our TITAN GPU servers and reduce your time to market, giving you a competitive edge.





















| Form Factor                            | 2U  |
|--|---|
| Chipset                                | Intel® C621   |
| Processor                              | Dual Intel® Xeon® Processor Scalable Family with TDP up to 205 W<br>Some PCIe or memory functions might be unavailable if only one (1) CPU is installed   |
| Memory Capacity                        | Up to 1,536 GB  |
| Memory Type and Size                   | RDIMM DDR4 ECC 2666 MHz. 8, 16, 32, and 64 GB<br>LRDIMM DDR4 ECC 2666 MHz. 8, 16, 32, and 64 GB   |
| Network Controller                     | (2) 10 Gb/s Base-T LAN ports (Intel® X550-AT2), and (1) dedicated management port   |
| GPU                                    | Up to (8) GPU cards. Dual root complex architecture.<br>Tesla® V100, Tesla® P40, Tesla® P4, Tesla® P100, Tesla® M60, Tesla® M40 24 GB, Tesla® M10   |
| Storage Controller                     | Onboard Intel® C621 6 Gb/s SATA controller. Supports RAID 0, 1, 5, 10. (Optional hardware RAID) (8) SAS/SATA ports, SATA 6 Gb/s, or SAS 12 Gb/s   |
| Drive Bays                             | (8) 2.5" HDD/SSD hot-swappable drives   |
| Expansion Slots                        | (8) PCle x16 (Gen3 x16 bus) for GPUs (full height, full length) (2) PCle x16 (Gen3 x16 bus) (low profile, half length) (1) OCP add-on card (option) System is validated for population with a uniform GPU model. Support is not provided for mixed GPU populations. For the latest GPU cards AVL, please contact your CIARA representative. |
| I/O Ports                              | (2) RJ45, (2) USB 3.0, (1) VGA, (1) MLAN  |
| System Management                      | Server Management (BMC) – IPMI 2.0 Compliant – iKVM   |
| Power Supply                           | 2200 W redundant (1+1) high efficiency 80 PLUS® Platinum Certified  |
| Environment                            | Operating: $50^{\circ}$ F to $95^{\circ}$ F ( $10^{\circ}$ C to $35^{\circ}$ C)<br>Non-operating: $-4^{\circ}$ F to $140^{\circ}$ F ( $-20^{\circ}$ C to $60^{\circ}$ C) @ $20^{\circ}$ K to $95^{\circ}$ K (non-condensing)  |
| Dimensions (DxWxH)                     | 31.5 in x 17.6 in x 3.4 in (800 mm x 448 mm x 87.5 mm)  |
| Warranty                               | CIARA's limited hardware warranty includes a one year, parts and labour with return to CIARA USA or Canada. Customers may purchase an extended warranty of up to 3 years on parts and labour with different support levels. Please contact CIARA at 1-877-242-7272 for complete warranty details including limitations and transferability. |
| *Refer to the Product AVL Document for | more information.   |

<sup>\*</sup>Refer to the Product AVL Document for more information.

## 1 (877) 242-7272 | sales@ciaratech.com | ciaratech.com

©2018 CIARA, a Hypertec brand. All rights reserved. "Intel, the Intel logo, Intel Core, Intel Inside, the Intel Inside logo, Intel vPro and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries." All other trademarks mentioned herein are the property of their respective owner. This document is only for informational purposes. Product specifications subject to change without notice.



Technology Provider

Platinum 2018

